**CLAIMS:** 

1. A low-pressure gas discharge lamp, which is equipped with a gas discharge vessel containing an inert gas filling as the buffer gas, and with electrodes and with means for generating and maintaining a low-pressure gas discharge, characterized in that it contains at least one tin halide.

5

- 2. A low-pressure gas discharge lamp as claimed in claim 1, characterized in that it contains  $2 \times 10^{-11}$  to  $2 \times 10^{-9}$  mole/cm<sup>3</sup> of tin halides in the gas phase.
- 3. A low-pressure gas discharge lamp as claimed in claims 1 and 2, characterized
  10 in that it contains approximately 2 x 10<sup>-10</sup> mole/cm<sup>3</sup> of tin halides in the gas phase,
  corresponding to an operational pressure of approximately 10 μbar.
  - 4. A low-pressure gas discharge lamp as claimed in any one of claims 1 to 3, characterized in that a wall temperature of  $T^* \pm 50$  K is set, wherein  $T^*$  is 220° C for tin chloride, 230° C for tin bromide, and 275° C for tin iodide.
  - 5. A low-pressure gas discharge lamp as claimed in any one of claims 1 to 4, characterized in that the gas pressure of the inert gas lies in the range between 1 and 5 mbar, and is preferably around 2 mbar.

20

15

- 6. A low-pressure gas discharge lamp as claimed in any one of claims 1 to 5, characterized in that the UV radiation emitted as a result of the discharge is converted into visible radiation by means of suitable fluorescent materials.
- 7. A low-pressure gas discharge lamp as claimed in any one of claims 1 to 6, characterized in that the walls of the discharge device comprise quartz, Al<sub>2</sub>O<sub>3</sub>, yttrium-aluminum garnet, or similar known materials.

- 8. A low-pressure gas discharge lamp as claimed in any one of claims 1 to 7, characterized in that the discharge can be excited inductively or capacitively with external electrodes and a high-frequency alternating field.
- 5 9. A low-pressure gas discharge lamp as claimed in any one of claims 1 to 8, characterized in that the internal electrodes comprise conductive materials (for example tungsten or rhenium).
- 10. A low-pressure gas discharge lamp as claimed in any one of claims 1 to 9, characterized in that it contains internal electrodes which are additionally provided with a material of low work function.